



CUTAWAY SECTION
(TO BE USED WITH ATU MODEL B-550 & B-800)

| ATU | | PUMP COMPARTMENT | | | | | FLOAT TETHER LENGTH | | |
|-------|-----|------------------|-----|---------------|---------------|--------------|---------------------|---------------|--------------|
| MODEL | GPD | SIZE | A | B | C | D | HIGH WTR ALARM | PUMP OVERRIDE | PUMP CONTROL |
| B-550 | 600 | 768 GAL | 53" | 15" (209 GAL) | 24" (347 GAL) | 8" (121 GAL) | 7" | 8" | 10" |
| B-800 | 800 | 854 GAL | 54" | 15" (233 GAL) | 25" (373 GAL) | 8" (119 GAL) | 7" | 8" | 10" |

* FLOAT CONFIGURATION CAN BE CHANGED IF REQUIRED

NOTE:

MAXIMUM BURIAL DEPTH TO BE 40" FROM SLAB TOP TO GRADE.



9235 Main Street #1
P.O. Box 507
Needville, Texas, 77461
1-888-331-5871

"Providing Concrete Environmental Solutions"

**STANDARD
FLOAT CONFIGURATION
FOR B-550 & B-800
AEROBIC TREATMENT UNITS**

NC-008-034

Scale: N.T.S.
* All Dimensions subject to allowable specification tolerances.

Date: 03/10/22

Rev Date: 11/18/22

Approved By: _____ Date: _____